

```
!
! Copyright (c) 2007-2008 by Sage Software Canada Ltd

def class "ConfigAppserverActionListener"

    like "AbstractActionListener"
    like "EventManagerObserver"

    ! Override values for description / NotificationFlag
    local theDescription$ = "Configure ProvideX Application Server"

    function Init()                                init
    function ActionPerformed(inActionEventID)      action_performed

end def

init:
    _OBJ'Init( from "AbstractActionListener" )
return

action_performed:                                ! executed when selected from contributed tools dialog
    local oCommon
    oCommon=new ("ecCommon")

    def object oEvtMgrFactory, "[wdx]com.pvx.ooadide.eventmanager.EventManagerFactory"
    EventMgr = oEvtMgrFactory'getEventManager()

    ! Set parameters for the JavX session
    javxArgs$ += "program=*appserv/config; "
    if oCommon'OSisWindows() {
        javxArgs$ += "defplaintextfontname=Courier New; graphicfontname=MS Sans Serif; "
    }
    javxArgs$ += "guiFactoryClassName=com.pvx.ooadide.views.rcp.RcpEmbedJavXView; "

    ! Start a JavX session in a new View for the Application Server Configuration
    EventMgr'runProgramInView(javxArgs$)

    drop object oEvtMgrFactory
    drop object oCommon
return
end
```