

```
!
! Copyright (c) 2007-2008 by Sage Software Canada Ltd

def class "ConfigWebserverActionListener"

    like "AbstractActionListener"
    like "EventManagerObserver"

    ! Override values for description
    local theDescription$ = "Configure ProvideX Web Server"

    function Init()                                init
    function ActionPerformed(inActionEventID)      action_performed
    function GetDescription$()                     get_description

end def

init:
    _OBJ'Init( from "AbstractActionListener" )
return

action_performed:                                ! executed when selected from contributed tools dialog
    local oCommon
    oCommon=new ("ecCommon")

    def object oEvtMgrFactory, "[wdx]com.pvx.ooadide.eventmanager.EventManagerFactory"
    EventMgr   = oEvtMgrFactory'getEventManager()

    ! Set parameters for the JavX session
    javxArgs$ += "program=*web/webcfg; "
    if oCommon'OSisWindows() {
        javxArgs$ += "deftextplanefontname=Courier New; graphicfontname=MS Sans Serif; "
        javxArgs$ += "minimumfontsize=10; graphicfontsize=11; fontsize=13; "
    }
    javxArgs$ += "guiFactoryClassName=com.pvx.ooadide.views.rcp.RcpEmbedJavXView; "

    ! Start a JavX session in a new View for the Application Server Configuration
    EventMgr'runProgramInView(javxArgs$)

    drop object oEvtMgrFactory
    drop object oCommon
return

end
```